

View Online at <https://aerobasegroup.com/nsn/5930-00-867-1362>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.484 inches single mounting facility and 0.516 inches single mounting facility

**Overall Length:**

Between 3.047 inches and 3.110 inches

**Overall Height:**

Between 1.469 inches and 1.500 inches

**Overall Width:**

Between 1.296 inches and 1.328 inches

**Shaft Diameter:**

0.234 inches single actuator and 0.266 inches single actuator

**Shaft Length:**

0.859 inches single actuator and 0.891 inches single actuator

**Nonturn Device Radius:**

0.515 inches at 9: 00 o'clock and 0.547 inches at 9: 00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 3rd section front

**Throw Quantity:**

7 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop-breakoff tab single actuator

**Contact Load Current Rating:**

1.5 amperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0