

View Online at <https://aerobasegroup.com/nsn/5930-00-867-5853>

Thread Class:

2b all threaded hole

Overall Height:

5.844 inches

Overall Width:

1.656 inches

Body Length:

3.188 inches

Body Height:

2.750 inches

Longest Horizontal Distance Between Mounting Centers:

2.810 inches

Longest Vertical Distance Between Mounting Centers:

2.380 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and threaded hole

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+100.00 actuation point pounds per square inch and +0.00/+100.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point hex nut and internal actuation point hex nut

Contact Stimulus Rating:

10.00 actuation point pounds per square inch and 7.00 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0