## NSN 5930-00-867-5853

Pressure Switch - Page 1 of 2

square inch



View Online at https://aerobasegroup.com/nsn/5930-00-867-5853

Thread Class:
2b all threaded hole
Overall Height:
5.844 inches
Overall Width:
1.656 inches
Body Length:
3.188 inches
Body Height:
2.750 inches
Longest Horizontal Distance Between Mounting Centers:
2.810 inches
Longest Vertical Distance Between Mounting Centers:
2.380 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and threaded hole
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
15.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+0.00/+100.00 actuation point pounds per square inch and +0.00/+100.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point hex nut and internal actuation point hex nut
Contact Stimulus Rating:

10.00 actuation point pounds per square inch and 7.00 deactuation point pounds per square inch and 3.00 differential point pounds per

## NSN 5930-00-867-5853

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 230.0 ac at sea level first voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Rectangular Thread Series Designator: Unc all threaded hole Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0