

View Online at <https://aerobasegroup.com/nsn/5930-00-867-6888>

Overall Length:

1.264 inches

Overall Diameter:

0.600 inches

Unthreaded Mounting Hole Diameter:

0.120 inches single mounting facility and 0.130 inches single mounting facility

Nonturn Device Radius:

0.380 inches at 9: 00 o'clock and 0.400 inches at 9: 00 o'clock

Individual Section Quantity:

1

Knob Specificationial Markings:

White indicator

Nonturn Device Type:

Tab at 9: 00 o'clock

Longest Horizontal Distance Between Mounting Centers:

0.9320 inches single mounting facility and 0.9425 inches single mounting facility

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

5 single section front

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.25 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0