

View Online at <https://aerobasegroup.com/nsn/5930-00-868-1249>

**Thread Class:**

2b single pressure connection

**Inside Diameter:**

0.438 inches single connection

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

5.938 inches

**Overall Height:**

6.874 inches

**Overall Width:**

2.812 inches

**Body Height:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

20.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, double break, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

16.0 amperes inductive load first voltage 8.0 amperes inductive load second voltage 4.0 amperes inductive load third voltage 3.2 amperes inductive load fourth voltage 9.6 amperes inductive load fifth voltage 4.8 amperes inductive load sixth voltage 2.5 amperes inductive load seventh voltage 2.0 amperes inductive load eighth voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

1.08 actuation point pounds per square inch absolute and 4.91 actuation point pounds per square inch absolute

**Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage230.0 ac at sea level second voltage440.0 ac at sea level third voltage550.0 ac at sea level fourth voltage115.0 dc at sea level fifth voltage230.0 dc at sea level sixth voltage440.0 dc at sea level seventh voltage550.0 dc at sea level eighth voltage

**Pressure Connector Type:**

Swivel nut, flare, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0