NSN 5930-00-868-2529

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-868-2529

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 3.844 inches **Overall Height:** 1.750 inches **Overall Width:** 2.250 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.625 inches single actuator **Nonturn Device Radius:** 0.500 inches at 12: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Tab at 12: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 8 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 120.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 8 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

NSN 5930-00-868-2529

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load ac at sea level **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0