NSN 5930-00-868-4208

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-868-4208

Body Style:
Bushing mounted
Overall Length:
2.355 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Bushing Length:
1.000 inches
Body Length:
0.980 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.375 inches
Actuator Free Position Height:
1.375 inches
Actuator Adapter Style:
Pushbutton
Adapter Bushing Length:
1.000 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Switch Release Force:
64.0 ounces
Switch Actuating Force:

Actuator Movement:

Between 96.0 ounces and 192.0 ounces

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

NSN 5930-00-868-4208

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

inductive ac
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0