

View Online at <https://aerobasegroup.com/nsn/5930-00-868-4222>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.245 inches and 0.255 inches

Body Height:

Between 0.490 inches and 0.530 inches

Unthreaded Mounting Hole Diameter:

Between 0.084 inches and 0.094 inches

Actuator Style:

Round

Actuator Free Position Height:

0.446 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

22.0 ounces

Actuator Movement:

Between 0.026 pretravel inches and 0.007 overtravel inches and 0.001 differential inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes motor ac

Test Data Document:

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0