

View Online at <https://aerobasegroup.com/nsn/5930-00-868-8719>

Thread Length:

0.359 inches single mounting facility and 0.391 inches single mounting facility

Overall Length:

2.016 inches

Overall Height:

2.375 inches

Overall Width:

2.000 inches

First Flat Length:

0.234 inches single actuator and 0.266 inches single actuator

Flat Height:

0.213 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.234 inches single actuator and 0.266 inches single actuator

Shaft Length:

0.213 inches single actuator and 0.223 inches single actuator

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-0.0/+75.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

2 2nd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Shaft Flat/slot Angular Location:

325.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

24 2nd actuator

Shaft Type:

Round, flatted single actuator

Contact Switching Action:

Makes before breaks each section front

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

0.5 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0