

View Online at <https://aerobasegroup.com/nsn/5930-00-869-1186>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.234 inches single mounting facility and 0.266 inches single mounting facility

**Overall Length:**

Between 5.969 inches and 6.031 inches

**Overall Height:**

2.328 inches

**Overall Width:**

2.000 inches

**Shaft Diameter:**

0.248 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.859 inches single actuator and 0.891 inches single actuator

**Nonturn Device Radius:**

0.515 inches at 12: 00 o'clock and 0.547 inches at 12: 00 o'clock

**Individual Section Quantity:**

10

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

28 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

28 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

12.8 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Test Data Document:**

13499-259-1484-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0