

View Online at <https://aerobasegroup.com/nsn/5930-00-869-1204>

Thread Class:

2a single mounting facility

Thread Length:

0.234 inches single mounting facility and 0.266 inches single mounting facility

Overall Length:

1.922 inches

Overall Height:

1.328 inches

Overall Width:

1.297 inches

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.609 inches single actuator and 0.641 inches single actuator

Nonturn Device Radius:

0.531 inches at 9:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 9:00 o'clock

Operating Temperature Range:

-65.0/+100.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

4 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0