NSN 5930-00-869-1624

Rotary Switch Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-869-1624

Overall Height: 1.328 inches Overall Widh: 1.297 inches Body Thickness: 0.062 inches Unthreaded Mounting Hole Diameter: 0.115 inches single mounting facility Longest Horizontal Distance Between Mounting Centers: 1.031 inches single mounting facility Operating Tempurature Range: -65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two outmmy contacts on front at positions 11, and 12 Precious Material And Location: Cilye Syleb Designator: Switch section, rotary Sherd Life: Na Naterial And Location:		
Overall Width: 1.297 inches Body Thickness: 0.062 inches Unthreaded Mounting Hole Diameter: 0.115 inches single mounting facility Longest Horizontal Distance Between Mounting Centers: 1.031 inches single mounting facility Operating Tempurature Range: 65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Contact Switching Action: Nakes before breaks single section front Contact Load Current Rating: 1.0 ampres resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Cilps and rotor blades silver Precious Material		-
1.297 indes Body Thickness: 0.062 inches Unthreaded Mounting Hole Diameter: 0.115 inches single mounting facility Longest Horizontal Distance Between Mounting Centers: 1.031 inches single mounting facility Operating Tempurature Range: -65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Clip Contact Switching Action: Nakes before breaks single section front Contact Load Current Rating: 1.0 ampers resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material: Silver Sylter Sylter Sylter Silver Silver Silver Silver Sylte besignator: Switch section,		
Body Thickness: 0.062 inches Unthreaded Mounting Hole Diameter: 0.115 inches single mounting facility Longest Horizontal Distance Between Mounting Centers: 1.031 inches single mounting facility Operating Tempurature Range: -65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility: Terminal Type: Clip Contact Load Current Rating: 1.0 amperes resistive load at at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips Silver Style Designator: Switch Section, rotary Sheff Life: Na Unt Of Measure: - Periadity Pattern: Na Big Life Section, rotary Shef		
Over a state of the state	-	
Unthreaded Mounting Hole Diameter: 0.115 inches single mounting facility Longest Horizontal Distance Between Mounting Centers: 1.031 inches single mounting facility Operating Tempurature Range: -65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Sheff Life: N/a Unit Of Measure: Pemilitarization: No	Body T	hickness:
0.115 inches single mounting facility Longest Horizontal Distance Between Mounting Centers: 1.031 inches single mounting facility Operating Tempurature Range: -65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Clips and rotor blades silver Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	0.062 ir	nches
Longest Horizontal Distance Between Mounting Centers: 1.031 inches single mounting facility Operating Tempurature Range: -65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load act at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Sheff Life: Na Emilitarization: No	Unthre	aded Mounting Hole Diameter:
1.031 inches single mounting facility Operating Tempurature Range: -65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Syle Designator: Switch section, rotary Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	0.115 ir	nches single mounting facility
Operating Tempurature Range: -65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Clips and rotor blades silver Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Syle Designator: Switch section, rotary Sheff Life: N/a Unit Of Measure: To Paesition: No Fig:	Longes	st Horizontal Distance Between Mounting Centers:
-65.0/+85.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Syle Designator: Switch section, rotary Shelf Life: N/a Unit of Measure: " Demilitarization: No Fig:	1.031 ir	nches single mounting facility
Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Syle Designator: Switch section, rotary Shelf Life: N/a Unit of Measure: To Demilitarization: No Fig:	Operat	ing Tempurature Range:
Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material Precious Material Silver Syle Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Image: Totar Summetrication:	-65.0/+8	85.0 degrees celsius
Mounting Method: Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Syle Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Fig:	Switch	Contact Basic Design:
Strut single mounting facility and unthreaded hole single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Coltact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: T Demilitarization: No Fig:	Nonpile	e-up nonsymmetrical
Contact Voltage Rating In Volts: 28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Mounti	ng Method:
28.0 dc at sea level Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Syle Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Strut si	ngle mounting facility and unthreaded hole single mounting facility
Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Contac	t Voltage Rating In Volts:
Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Sheff Life: N/a Unit Of Measure: Penalitarization: No Fig:	28.0 dc	at sea level
Terminal Type: Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Mounti	ng Facility Pattern:
Clip Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Dint Of Measure: Demilitarization: No Fig:	Two po	sition in-line single mounting facility
Contact Switching Action: Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Material Component State Precious Material: Silver Sheff Life: N/a Unit Of Measure: Mo Fig:	Termin	al Type:
Makes before breaks single section front Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Clip	
Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Contac	t Switching Action:
1.0 amperes resistive load ac at sea level Special Features: Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Makes	before breaks single section front
Special Features:Two dummy contacts on front at positions 11, and 12Precious Material And Location:Clips and rotor blades silverPrecious Material:SilverSilverStyle Designator:Switch section, rotaryShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Contac	t Load Current Rating:
Two dummy contacts on front at positions 11, and 12 Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.0 amp	peres resistive load ac at sea level
Precious Material And Location: Clips and rotor blades silver Precious Material: Silver Style Designator: Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specia	I Features:
Clips and rotor blades silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Two du	mmy contacts on front at positions 11, and 12
Precious Material:SilverStyle Designator:Switch section, rotaryShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Precio	us Material And Location:
Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Clips ar	nd rotor blades silver
Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Preciou	us Material:
Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Silver	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style D	esignator:
N/a Unit Of Measure: Demilitarization: No Filg:	Switch	section, rotary
Unit Of Measure: Demilitarization: No Fiig:	Shelf L	ife:
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of	Measure:
No Fiig:		
No Fiig:	Demilit	arization:
-	No	
-	Fiiq:	
	-)