NSN 5930-00-869-5949

Pressure Switch - Page 1 of 2

Thread Class:

Inside Diameter:

2b single pressure connection



View Online at https://aerobasegroup.com/nsn/5930-00-869-5949

0.438 inches single connection **Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 5.188 inches **Overall Height:** 5.874 inches **Overall Width:** 2.812 inches **Body Height:** 2.750 inches **Unthreaded Mounting Hole Diameter:** 0.281 inches **Longest Horizontal Distance Between Mounting Centers:** 2.406 inches **Shortest Horizontal Distance Between Mounting Centers:** 0.656 inches **Longest Vertical Distance Between Mounting Centers:** 3.281 inches **Pressure Switch Type:** Gage **Mounting Method:** Bracket and unthreaded hole **Features Provided:** Electrical access port **Contact Action Stimulus:** Increase **Proof Pressure:** 80.00 pounds per square inch gage **Thread Size:** 0.438 inches single pressure connection **Mounting Facility Pattern:** Isosceles triangle **Nonpile-up Contact Arrangement:**

Contact Load Current Rating:

Terminal Type:

Screw

1 pole, single throw, normally closed, momentary action

16.0 amperes inductive load first voltage8.0 amperes inductive load second voltage4.0 amperes inductive load third voltage3.2 amperes inductive load fourth voltage9.6 amperes inductive load fifth voltage4.8 amperes inductive load sixth voltage2.5 amperes inductive load seventh voltage2.0 amperes inductive load eighth voltage

NSN 5930-00-869-5949

Pressure Switch - Page 2 of 2

A048b0



Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+4.00/+35.00 actuation point pounds per square inch gage
Contact Adjustment Type:
Internal actuation point screw
Contact Voltage Rating In Volts:
115.0 ac at sea level first voltage230.0 ac at sea level second voltage440.0 ac at sea level third voltage550.0 ac at sea level fourth
voltage115.0 dc at sea level fifth voltage230.0 dc at sea level sixth voltage440.0 dc at sea level seventh voltage550.0 dc at sea level eighth
voltage
Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: