NSN 5930-00-870-4572

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-870-4572

Body Style:					
Hole mounted					
Hazardous Locations/environmental Protection:					
Oiltight					
Actuator Length:					
3.000 inches					
Actuator Style:					
Roller arm					
Actuator Height:					
1.109 inches					
Actuator Roller Diameter:					
0.750 inches					
Actuator Roller Width:					
0.281 inches					
Housing Height:					
1.531 inches					
Housing Length:					
2.844 inches					
Housing Width:					
1.781 inches					
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:					
2.344 inches					
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:					
1.156 inches					
Maximum Voltage Rating In Volts:					
600.0 ac and 600.0 dc					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Unthreaded hole					
Nonpile-up Contact Arrangement:					
1 two circuit, double break/double make, one position momentary single switch unit					
Switch Actuating Force:					
48.0 inch-ounces					
Actuator Movement:					
12.0 pretravel degrees and 49.0 overtravel degrees and 6.0 differential degrees					
Contact Load Current Rating At Maximum Rated Voltage:					

Special Features:

Adjustable lever height

Terminal Type And Quantity:

0.100 amperes resistive dc and 1.200 amperes resistive ac

4 screw

NSN 5930-00-870-4572

Sensitive Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0