## NSN 5930-00-870-6352

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-870-6352

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
1.150 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
1.026 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.406 inches
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
0.150 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
0.75 ounces
Switch Actuating Force:
3.5 ounces
Actuator Movement:
Between 0.218 pretravel inches and 0.156 overtravel inches and 0.005 differential inches and 0.040 differential inches
Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

## **NSN 5930-00-870-6352** Sensitive Switch - Page 2 of 2



<b>Precious Material And Location:</b>
Contacts silver
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0