

View Online at <https://aerobasegroup.com/nsn/5930-00-870-6352>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.150 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Length:

1.026 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.406 inches

Actuator Roller Diameter:

0.370 inches

Actuator Roller Width:

0.150 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

0.75 ounces

Switch Actuating Force:

3.5 ounces

Actuator Movement:

Between 0.218 pretravel inches and 0.156 overtravel inches and 0.005 differential inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0