

View Online at <https://aerobasegroup.com/nsn/5930-00-870-8016>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.872 inches and 0.878 inches

**Body Length:**

Between 1.079 inches and 1.109 inches

**Body Width:**

0.400 inches

**Body Height:**

Between 0.610 inches and 0.640 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.113 inches and 0.116 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.403 inches and 0.409 inches

**Actuator Length:**

0.810 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 0.780 inches and 0.840 inches

**Actuator Roller Diameter:**

0.190 inches

**Actuator Roller Width:**

0.190 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 125.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

8.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.040 overtravel inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0