

View Online at <https://aerobasegroup.com/nsn/5930-00-871-0992>

**Thread Class:**

3b all pressure connection

**Inside Diameter:**

0.250 inches all connections

**Overall Length:**

3.562 inches

**Overall Height:**

5.312 inches

**Overall Width:**

1.906 inches

**Body Length:**

2.656 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained

**Terminal Type:**

Connector, plug

**Contact Load Current Rating:**

4.6 amperes motor load fourth voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point adjustable, preset

**Contact Adjustment Range:**

+150.00/+450.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point knob

**Contact Stimulus Rating:**

345.00 actuation point pounds per square inch and 355.00 actuation point pounds per square inch and 450.00 deactuation point pounds per square inch and 100.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

230.0 dc at sea level third voltage

**Pressure Connector Type:**

Flare, threaded internal all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Ptf-sae short all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0