## NSN 5930-00-871-2537

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-871-2537

| Thread Class:                                 |
|---|
| 2a single mounting facility                   |
| Thread Length:                                |
| 0.375 inches single mounting facility         |
| Hazardous Locations/environmental Protection: |
| Dustproof                                     |
| Overall Length:                               |
| 3.716 inches                                  |
| Overall Height:                               |
| 1.281 inches                                  |
| Overall Width:                                |
| 1.281 inches                                  |
| Shaft Diameter:                               |
| 0.250 inches single actuator                  |
| Shaft Length:                                 |
| 1.875 inches single actuator                  |
| Nonturn Device Radius:                        |
| 0.531 inches at 3: 00 o'clock                 |
| Individual Section Quantity:                  |
| 3   |
| Nonturn Device Type:                          |
| Tab at 3: 00 o'clock                          |
| Switch Contact Basic Design:                  |
| Nonpile-up symmetrical                        |
| Pole Quantity:                                |
| 1 each section front                          |
| Throw Quantity:                               |
| 5 each section front                          |
| Mounting Method:                              |
| Threaded bushing single mounting facility     |
| Thread Size:                                  |
| 0.375 inches single mounting facility         |
| Contact Voltage Rating In Volts:              |
| 28.0 dc at sea level                          |
| Switch Actuator Indexing Position Quantity:   |
| 5 single actuator                             |
| Shaft Type:                                   |
| Round single actuator                         |
| Terminal Type:                                |
| Tab w/screw                                   |
| Contact Switching Action:                     |

Contact Owntoning Action:

Breaks before makes each section front

## NSN 5930-00-871-2537

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 450.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Clips and rotor contacts silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A052b0