

View Online at <https://aerobasegroup.com/nsn/5930-00-872-1671>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant and explosion proof

Overall Length:

4.160 inches

Body Diameter:

1.000 inches

Bushing Length:

0.540 inches

Body Length:

2.600 inches

Overall Diameter:

1.000 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.422 inches

Actuator Height:

1.020 inches

Actuator Position-action Relationship:

Center position maintained and left position maintained and right position maintained

Actuator Position-locking Relationship:

Center position locked in and left position locked in and right position locked in

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 2.000 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0