

View Online at <https://aerobasegroup.com/nsn/5930-00-872-1671>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant and explosion proof

**Overall Length:**

4.160 inches

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.540 inches

**Body Length:**

2.600 inches

**Overall Diameter:**

1.000 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.422 inches

**Actuator Height:**

1.020 inches

**Actuator Position-action Relationship:**

Center position maintained and left position maintained and right position maintained

**Actuator Position-locking Relationship:**

Center position locked in and left position locked in and right position locked in

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Holding solenoid

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 2.000 amperes inductive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0