## NSN 5930-00-872-4938

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-872-4938
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
6.251 inches
Overall Height:
2.812 inches
Overall Width:
2.812 inches
Individual Section Quantity:
5
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-74290piece28
Longest Horizontal Distance Between Mounting Centers:
2.297 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.297 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section periphery
Throw Quantity:
2 each section periphery
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator

**Terminal Type:** 

Screw

## NSN 5930-00-872-4938

Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig: A052b0