

View Online at <https://aerobasegroup.com/nsn/5930-00-872-6782>

Thread Class:

2a 2nd mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.020 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.100 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.688 inches

Nonturn Device Radius:

0.250 inches at 3: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 3: 00 o'clock

Longest Horizontal Distance Between Mounting Centers:

0.500 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

8 each section rear

Mounting Method:

Threaded stud 2nd mounting facility

Thread Size:

0.250 inches 1st mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+5.000/+15.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level and 120.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0