

View Online at <https://aerobasegroup.com/nsn/5930-00-872-6782>

**Thread Class:**

2a 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.020 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.100 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Overall Diameter:**

0.688 inches

**Nonturn Device Radius:**

0.250 inches at 3: 00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Longest Horizontal Distance Between Mounting Centers:**

0.500 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

8 each section rear

**Mounting Method:**

Threaded stud 2nd mounting facility

**Thread Size:**

0.250 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

195.0 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:**

1 each section

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+5.000/+15.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level and 120.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0