Thermostatic Switch - Page 1 of 2

60.0 first voltage



View Online at https://aerobasegroup.com/nsn/5930-00-872-7735

Hazardous Locations/environmental Protection: Vaportight, gastight **Overall Length:** 1.217 inches **Overall Height:** 0.500 inches **Body Diameter:** 0.572 centimeters Mounting Slot Width: Between 0.133 inches and 0.147 inches **Body Height:** 0.364 inches **Unthreaded Mounting Hole Diameter:** Between 0.133 inches and 0.147 inches **Distance Between Mounting Facility Centers:** Between 0.930 inches and 0.944 inches Tempurature Sensing Element Type: Disc **Operating Tempurature Rating:** Between -80.0 degrees fahrenheit and 500.0 degrees fahrenheit **Mounting Method:** Bracket and unthreaded hole and slot **Features Provided:** Hermetically sealed case **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load fourth voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 136.00 actuation point degrees fahrenheit and 146.00 actuation point degrees fahrenheit and 125.00 deactuation point degrees fahrenheit and 135.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 30.0 dc at sea level fourth voltage **Frequency In Hertz:**

NSN 5930-00-872-7735

Thermostatic Switch - Page 2 of 2



Media For Which Designed: Gas or liquid **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Disc w/flange Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A048b0