

View Online at <https://aerobasegroup.com/nsn/5930-00-872-8166>

Thread Class:

2a single mounting facility

Thread Length:

0.313 inches single mounting facility

Width Between Flats:

0.182 inches single actuator and 0.184 inches single actuator

Overall Length:

4.406 inches

Overall Height:

1.594 inches

Overall Width:

1.422 inches

First Flat Length:

0.240 inches single actuator and 0.260 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.750 inches single actuator

Individual Section Quantity:

6

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0