## NSN 5930-00-872-9272

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-872-9272

Body Style:
Hole mounted
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Height:
0.930 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.250 inches
Housing Length:
4.340 inches
Housing Width:
1.370 inches
Maximum Voltage Rating In Volts:
480.0 ac and 550.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
Switch Actuating Force: 48.0 ounces
-
48.0 ounces
48.0 ounces Actuator Movement:
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:  100.000 milliamperes resistive dc and 10.000 amperes resistive ac
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:  100.000 milliamperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:  100.000 milliamperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  4 screw
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:  100.000 milliamperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  4 screw  Shelf Life:
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:  100.000 milliamperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  4 screw  Shelf Life:  N/a
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:  100.000 milliamperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  4 screw  Shelf Life:  N/a
48.0 ounces  Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:  100.000 milliamperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity:  4 screw  Shelf Life:  N/a  Unit Of Measure:
Actuator Movement:  Between 20.0 pretravel degrees and 30.0 overtravel degrees and 12.0 differential degrees  Contact Load Current Rating At Maximum Rated Voltage:  100.000 milliamperes resistive dc and 10.000 amperes resistive ac  Terminal Type And Quantity: 4 screw  Shelf Life: N/a  Unit Of Measure:  Demilitarization: