## NSN 5930-00-872-9363

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-872-9363

**Thread Class:** 

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

**Overall Length:** 

1.968 inches

**Overall Height:** 

2.312 inches

**Overall Width:** 

1.968 inches

First Flat Length:

0.343 inches single actuator

Flat Height:

0.216 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.656 inches single actuator

**Nonturn Device Radius:** 

0.530 inches at 9: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 9: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

6 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

320.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:** 

6 single actuator

## **NSN 5930-00-872-9363**Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
15.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level
Style Designator:
Circular wafer, bushing mount
Test Data Document:
81349-mils3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0