

View Online at <https://aerobasegroup.com/nsn/5930-00-874-1785>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.364 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Width:

0.400 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Free Position Height:

0.625 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 14.0 ounces

Actuator Movement:

Between 0.047 pretravel inches and 0.040 overtravel inches and 0.006 differential inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0