NSN 5930-00-874-4061

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-874-4061

| Hazardous Locations/environmental Protection: |
|---|
| Moisture resistant and salt spray resistant |
| Overall Length: |
| 2.410 inches |
| Overall Height: |
| 0.560 inches |
| Overall Width: |
| 1.779 inches |
| Actuator Style: |
| Rectangular |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 30.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac |
| Special Features: |
| 2 mtg holes spaced 1.467 in. C to c |
| Precious Material And Location: |
| Contacts silver or contacts gold |
| Unable To Decode: |
| Unable to decode or unable to decode |
| Terminal Type And Quantity: |
| 6 turret and 5 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |
| |