## NSN 5930-00-874-4820

Pressure Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-874-4820

| view Online at https://aerobasegroup.com/hsi//3930-00-8/4-4820 |
|--|
| Hazardous Locations/environmental Protection:                  |
| Watertight   |
| Overall Length:  |
| 5.812 inches   |
| Overall Height:  |
| 2.688 inches   |
| Overall Width:   |
| 5.000 inches   |
| Longest Horizontal Distance Between Mounting Centers:          |
| 2.406 inches   |
| Shortest Horizontal Distance Between Mounting Centers:         |
| 0.656 inches   |
| Longest Vertical Distance Between Mounting Centers:            |
| 3.281 inches   |
| Pressure Switch Type:  |
| Gage   |
| Mounting Method:   |
| Bracket  |
| Contact Action Stimulus:                                       |
| Increase   |
| Nonpile-up Contact Arrangement:                                |
| 1 pole, single throw, normally closed, momentary action        |
| Terminal Type:   |
| Tab w/screw  |
| Contact Load Current Rating:                                   |
| 2.0 amperes resistive load first voltage                       |
| Contact Adjustability:   |
| Actuation point adjustable                                     |
| Contact Adjustment Type:                                       |
| External actuation point screw                                 |
| Contact Voltage Rating In Volts:                               |
| 550.0 ac at sea level first voltage                            |
| Frequency In Hertz:  |
| 60.0 second voltage  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A048b0   |
|  |