NSN 5930-00-875-0874

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-875-087
Width Between Flats:
0.186 inches single actuator
Overall Length:
2.626 inches
Overall Height:
1.750 inches
Overall Width:
1.750 inches
First Flat Length:
0.813 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.938 inches single actuator
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
1.375 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.375 inches single mounting facility
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section rear
Throw Quantity:
5 single section rear
Mounting Method:
Bracket single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Shaft Flat/slot Angular Location:
90.0 degrees from contact position 1 single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
5 single actuator
Shaft Type:
Round, parallel flatted single actuator
Terminal Type:

Turret

NSN 5930-00-875-0874

Rotary Switch - Page 2 of 2



Con	tact	Swit	chino	ı Acti	on:
OUL	ıavı	OWIL	CHILL	ı Actı	vii.

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+2.000/+4.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0