

View Online at <https://aerobasegroup.com/nsn/5930-00-876-1634>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.870 inches

Overall Height:

3.150 inches

Overall Width:

1.540 inches

Body Height:

2.890 inches

Capillary Tube Length:

60.0 inches

Bulb Length:

5.620 inches

Bulb Diameter:

0.370 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Flush

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.8 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+40.00/+90.00 actuation point degrees fahrenheit and +38.25/+88.25 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Stimulus Rating:

65.00 actuation point degrees fahrenheit and 1.75 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0