

View Online at <https://aerobasegroup.com/nsn/5930-00-876-1634>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.870 inches

**Overall Height:**

3.150 inches

**Overall Width:**

1.540 inches

**Body Height:**

2.890 inches

**Capillary Tube Length:**

60.0 inches

**Bulb Length:**

5.620 inches

**Bulb Diameter:**

0.370 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Flush

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

5.8 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable, preset

**Contact Adjustment Range:**

+40.00/+90.00 actuation point degrees fahrenheit and +38.25/+88.25 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point shaft and external actuation point shaft

**Contact Stimulus Rating:**

65.00 actuation point degrees fahrenheit and 1.75 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

240.0 ac at sea level first voltage

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0