

View Online at <https://aerobasegroup.com/nsn/5930-00-876-6632>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.782 inches

Overall Height:

6.000 inches

Overall Width:

4.750 inches

First Flat Length:

1.125 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.813 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility and 0.410 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

3.781 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.781 inches single mounting facility

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

2 each section front

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

60.0 amperes resistive load dc at sea level

Precious Material And Location:

Terminal surfaces silver

Precious Material:

Silver

Style Designator:

Square wafer, panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0