NSN 5930-00-877-5626

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-877-5626

Thread Class:

3a single pressure connection

Overall Length:

2.500 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 135.0 degrees fahrenheit

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

120.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

180.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

7.00 actuation point pounds per square inch gage and 4.00 deactuation point pounds per square inch gage and 3.00 differential point

pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Special Features:

Two lock wire holes and four vent holes and one drive screw lock

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

NSN 5930-00-877-5626

Pressure Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0

