## NSN 5930-00-877-9583

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-877-9583

**Thread Class:** 2a single mounting facility Thread Length: 0.312 inches single mounting facility **Overall Length:** 2.375 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.688 inches single actuator **Nonturn Device Radius:** 0.484 inches at 12: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 12: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 single section rear **Throw Quantity:** 4 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-877-9583

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
2.0 amperes resistive load ac at sea level
Precious Material And Location:
Contacts and terminals silver
Precious Material:
Silver
Style Designator:
Tap, square frame
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0