# NSN 5930-00-877-9584

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-877-9584

#### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.313 inches single mounting facility

### **Overall Length:**

3.501 inches

#### **Overall Height:**

1.900 inches

#### **Overall Width:**

1.750 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

1.000 inches single actuator

#### **Nonturn Device Radius:**

0.531 inches at 12: 00 o'clock

# Individual Section Quantity:

3

Nonturn Device Type:

Tab at 12: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

2 each section rear

#### **Throw Quantity:**

4 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

125.0 ac at sea level

#### Switch Actuator Indexing Position Quantity:

4 single actuator

## Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-877-9584

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 2.0 amperes resistive load ac at sea level Style Designator: Square wafer, panel mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0