

View Online at <https://aerobasegroup.com/nsn/5930-00-878-0345>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

2.760 inches

Overall Height:

2.300 inches

Overall Width:

1.000 inches

Bushing Length:

0.577 inches

Body Length:

1.060 inches

Body Width:

1.000 inches

Body Height:

1.750 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.700 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.120 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

Special Features:

Leads embedded and sealed with epoxy casting resin and sealer

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0