

View Online at <https://aerobasegroup.com/nsn/5930-00-878-1006>

Thread Class:

2a

Body Style:

Bushing mounted

Bushing Length:

Between 0.295 inches and 0.325 inches

Body Length:

Between 0.765 inches and 0.795 inches

Body Width:

0.906 inches

Body Height:

Between 0.965 inches and 0.995 inches

Actuator Diameter:

Between 0.308 inches and 0.395 inches

Actuator Height:

Between 0.175 inches and 0.325 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

End Application:

Qticonderoga class cg (47), yellowstone class ad-41, kidd class ddg, oliver perry class ffg, powatan class t-atf 166, usns henry j. Kaiser class tao, emory s. Island class as, iwo jima class lph; helicopter, ch-53/d/e

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0