

View Online at <https://aerobasegroup.com/nsn/5930-00-878-7593>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture proof

Overall Height:

1.280 inches

Body Diameter:

0.340 inches

Bushing Length:

0.280 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Height:

0.320 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.680 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 5.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0