

View Online at <https://aerobasegroup.com/nsn/5930-00-879-3593>

**Thread Length:**

0.375 inches single pressure connection

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

2.020 inches

**Overall Diameter:**

1.690 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Inlet connection

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

350.00 pounds per square inch

**Thread Size:**

0.125 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

4.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+30.00/+70.00 actuation point pounds per square inch and +30.00/+70.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point hex nut and external actuation point hex nut

**Contact Stimulus Rating:**

60.00 actuation point pounds per square inch and 10.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

6.0 dc at sea level second voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Ptf-sae short single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0