

View Online at <https://aerobasegroup.com/nsn/5930-00-879-3593>

Thread Length:

0.375 inches single pressure connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

2.020 inches

Overall Diameter:

1.690 inches

Pressure Switch Type:

Gage

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

350.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

4.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+30.00/+70.00 actuation point pounds per square inch and +30.00/+70.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Stimulus Rating:

60.00 actuation point pounds per square inch and 10.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

6.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Cylindrical

Thread Series Designator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0