## NSN 5930-00-879-4582

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-879-4582

Body Style:
Hole mounted
Overall Length:
0.850 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Width:
0.320 inches
Body Length:
0.850 inches
Body Width:
0.320 inches
Body Height:
0.968 inches
Unthreaded Mounting Hole Diameter:
0.112 inches
Actuator Length:
0.679 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.709 inches
Actuator Roller Diameter:
0.187 inches
Actuator Roller Width:
0.125 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
16.0 ounces
Actuator Movement:

Contact Load Current Rating At Maximum Rated Voltage:

Between 0.115 pretravel inches and 0.025 overtravel inches and 0.058 differential inches

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 10.000 amperes resistive ac

## NSN 5930-00-879-4582

Sensitive Switch - Page 2 of 2



Special Features:
36 in. Leads
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A053a0