## NSN 5930-00-880-2195

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-880-2195

view Online at https://aerobasegroup.com/hsh/osso-oo-ooo-2135
Body Style:
Bushing mounted
Overall Length:
1.594 inches
Overall Height:
0.875 inches
Overall Width:
0.875 inches
Bushing Length:
0.313 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
Between 0.365 inches and 0.385 inches
Actuator Height:
Between 0.240 inches and 0.260 inches
Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
120.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac
Test Data Document:
81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 tab, solder lug

N/a

Shelf Life:

## NSN 5930-00-880-2195

Push Switch - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0