

View Online at <https://aerobasegroup.com/nsn/5930-00-880-2312>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

0.626 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.183 inches and 0.193 inches

**Overall Height:**

0.695 inches

**Overall Width:**

0.326 inches

**Body Length:**

0.626 inches

**Body Width:**

0.326 inches

**Body Height:**

0.600 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.091 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.055 inches and 0.065 inches

**Actuator Height:**

0.095 inches

**Actuator Free Position Height:**

Between 0.405 inches and 0.445 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

17.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac and 4.000 amperes motor ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0