

View Online at <https://aerobasegroup.com/nsn/5930-00-880-2312>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

0.626 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.183 inches and 0.193 inches

Overall Height:

0.695 inches

Overall Width:

0.326 inches

Body Length:

0.626 inches

Body Width:

0.326 inches

Body Height:

0.600 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.091 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.055 inches and 0.065 inches

Actuator Height:

0.095 inches

Actuator Free Position Height:

Between 0.405 inches and 0.445 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac and 4.000 amperes motor ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0