NSN 5930-00-880-3296

Thermostatic Switch - Page 1 of 2

Hazardous Locations/environmental Protection:

Weatherproof



View Online at https://aerobasegroup.com/nsn/5930-00-880-3296

1.078 inches Overall Height: 0.605 inches Body Diameter: 0.605 inches Body Height: 0.290 inches Body Height: 0.290 inches Unthreaded Mounting Hole Diameter: 0.140 inches Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Overall Length:
0.605 inches Body Diameter: 0.605 inches Body Height: 0.290 inches Unthreaded Mounting Hole Diameter: 0.140 inches Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	1.078 inches
Body Diameter: 0.605 inches Body Height: 0.290 inches Unthreaded Mounting Hole Diameter: 0.140 inches Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Overall Height:
0.605 inches Body Height: 0.290 inches Unthreaded Mounting Hole Diameter: 0.140 inches Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	0.605 inches
Body Height: 0.290 inches Unthreaded Mounting Hole Diameter: 0.140 inches Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Body Diameter:
0.290 inches Unthreaded Mounting Hole Diameter: 0.140 inches Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	0.605 inches
Unthreaded Mounting Hole Diameter: 0.140 inches Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Body Height:
Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	0.290 inches
Distance Between Mounting Facility Centers: 0.937 inches Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Unthreaded Mounting Hole Diameter:
Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	0.140 inches
Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Distance Between Mounting Facility Centers:
Internal sensor Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	0.937 inches
Operating Tempurature Rating: Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Tempurature Sensing Element Type:
Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Internal sensor
Mounting Method: Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Operating Tempurature Rating:
Flange and unthreaded hole Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit
Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Mounting Method:
Hermetically sealed case Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Flange and unthreaded hole
Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Features Provided:
Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Hermetically sealed case
Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Contact Action Stimulus:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Increase
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Mounting Facility Pattern:
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Two position in-line
Terminal Type: Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Nonpile-up Contact Arrangement:
Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	1 pole, single throw, normally closed, momentary action
Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	
6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Terminal Type:
Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	
Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:	Tab, solder lug
Contact Stimulus Rating:	Tab, solder lug Contact Load Current Rating:
-	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage
	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability:
400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
Contact Voltage Rating In Volts:	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit
30.0 dc at sea level third voltage	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
30.0 dc at sea level third voltage Media For Which Designed:	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage
-	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed:
Media For Which Designed:	Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas
400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
Contact Voltage Rating In Volts:	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit
30.0 dc at sea level third voltage	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
-	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage
Media For Which Designed:	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed:
Media For Which Designed: Gas	Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas
Media For Which Designed: Gas	Tab, solder lug Contact Load Current Rating: 6.0 amperes resistive load third voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 400.00 actuation point degrees fahrenheit and 370.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas Style Designator:

NSN 5930-00-880-3296

Thermostatic Switch - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0