NSN 5930-00-880-7131

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-880-7131

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|--|
| 0.375 inches |
| Body Length: |
| 0.781 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.356 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.087 inches |
| Actuator Free Position Height: |
| 0.332 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 30.0 dc |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained single switch unit |
| Switch Release Force: |
| 1.0 ounces |
| Switch Actuating Force: |
| 5.0 ounces |
| Actuator Movement: |
| Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 3.000 amperes resistive dc and 5.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 3 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |
| |