

View Online at <https://aerobasegroup.com/nsn/5930-00-881-0243>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

Between 0.779 inches and 0.799 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.370 inches and 0.380 inches

Overall Height:

0.695 inches

Overall Width:

Between 0.240 inches and 0.260 inches

Body Length:

Between 0.779 inches and 0.799 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.450 inches and 0.510 inches

Case Material:

Plastic

Actuator Length:

Between 0.281 inches and 0.311 inches

Actuator Style:

Leaf

Actuator Free Position Height:

0.310 inches

Actuator Roller Diameter:

Between 0.026 inches and 0.036 inches

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0